

US009636278B2

(12) United States Patent

Sanders et al.

(10) Patent No.: US 9,636,278 B2

(45) **Date of Patent:** May 2, 2017

(54) SYSTEM FOR CLOSED TRANSFER OF FLUIDS WITH A LOCKING MEMBER

- (71) Applicant: **Becton Dickinson and Company Limited**, Dun Laoghaire (IE)
- (72) Inventors: Laurie Sanders, Glen Ridge, NJ (US); Yan Yevmenenko, New York, NY (US)
- (73) Assignee: **Becton Dickinson and Company Limited**, Dun Laoghaire (IE)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: 14/532,165
- (22) Filed: Nov. 4, 2014

(65) **Prior Publication Data**US 2015/0123398 A1 May 7, 2015

Related U.S. Application Data

- (60) Provisional application No. 61/900,674, filed on Nov. 6, 2013.
- (51) Int. Cl.

 A61J 1/20 (2006.01)

 A61M 39/10 (2006.01)

 (Continued)

(Continued)

(58) Field of Classification Search
CPC A61J 1/1406; A61J 1/1418; A61J 1/1481;
A61J 1/201; A61J 1/2055; A61J 1/2058;
(Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

FOREIGN PATENT DOCUMENTS

EP 2462971 A1 6/2012 WO 2004033023 A1 4/2004 (Continued)

Primary Examiner — Adam Marcetich (74) Attorney, Agent, or Firm — The Webb Law Firm

(57) ABSTRACT

A connector system for a medical device includes a first connector having an elongate opening, and a second connector including a lock portion, where the first connector is movable relative to the second connector between an initial position where the first connector is not in fluid communication with the second connector and an activated position where the first connector is in fluid communication with the second connector. The system also includes a locking member connected to the first connector. The locking member is transitionable between an unlocked position where the second connector is movable within the elongate opening of the first connector and a locked position where the locking member is configured to engage the lock portion of the second connector to lock the first connector to the second connector in the activated position. The locking member comprises a spring body received by the elongate opening of the first connector.

15 Claims, 72 Drawing Sheets

